

Pressure and Vaccum Pump HV 90 for Service and Maintenance

Pressure and Vacuum Pump HV 90 for service and maintenance pneumatic operated

- robust metal construction
- · simple one-hand operation
- pressure generation up to 42 psi (3 bar)
- switchable to vacuum generation up to -760 mmHg



HV 90 with included accessories

• pressure compound gauge with fine graduation and rubber protection included

The rugged pressure and vacuum pump **HV 90** is used for simple generation of pressure up to 42 psi (3 bar) and vaccum up to -760 mmHg (-0,9 bar) for service and maintenance purposes, e.g. inspection of pressure or vacuum components in plants, processed and vehicles.

A pressure gauge -760 mmHg / +42 PSI with fine graduation and rubber protection is included.

The pressure and vacuum pump **HV 90** must be used with dry media only. No fluids must get into the pump. If service and maintenance with fluid media is to be made, the optional drainage box **HVZ 02** must be mounted in front of the **HV 90**.



HVZ 02 drainage box

Order Codes and supply scope

Order-Code	Description
HV- 90	 pressure and vacuum pump HV 90 with tube connection pressure gauge with rubber protection transparent plastic tube 4 different tube adapters (plastic) 1 conical tube adapter (brass) carrying case
HVZ- 02	Drainage Box (120 ml) with tube connections (must be used if HV 90 may be contaminated with fluid media)
HV- 90- 2	pressure and vacuum, pump HV 90 with conn. /16-20 UNF (1/4" SAE) (e.g. testing of pressure/vacuum switches in air conditioning technology. carrying case

Note: For pressure calibration purposes we recommend our calibration hand pumps with fine variation valve and pressure relief valve (e.g. 2911/2941, LTP1, LPP 30...)



DRUCK & TEMPERATUR Leitenberger GmbH

Bahnhofstr. 33 • D-72138 Kirchentellinsfurt • Germany Tel.: +49-7121-90920-0 • Fax: +49-7121-90920-99

E-Mail: DT-Export@Leitenberger.de • http://www.Leitenberger.com

