

SAFETY
FIRST



HAEMATOKRIT 210
Special-purpose Centrifuge

HAEMATOKRIT 210

At 16,060 g sedimentation is completed in just a little over 6 minutes.

At any rate, a run time of 10 minutes is sufficient. The rotor comes to a braked standstill.

Each capillary is secured within its own chamber and supported by a holding tray. This holding tray serves to contain glass shards and any leakage should a tube break. It is easy to clean and disposable in the case of glass breakage.

Capillaries, to be used for quantitative buffy coat analysis are centrifuged in the 20-place rotor prior to further analysis.

HAEMATOKRIT 210 control panel



USER-FRIENDLINESS

- Quick-entry keypad
 - Easy-to-read, digital display
 - Display of current parameter values
- Easy entry of the parameters
 - RPM in increments of 100
 - Running time in minutes, max. 99 min

SAFETY

- Lid locking and holding
- Emergency lid lock release
- Motor overheating protection
- Imbalance switch-off
- Standstill indication

hematocrit rotor, 24-place

for standard capillaries, with lid as evaluation disc



Cat. No.	2076		
capillaries per rotor	24		
capillaries	basic	mylar-coated	self-sealing and mylar-coated
Cat. No.	2074	1072	1071
sealing putty			
Cat. No.	2077		



The holding trays are easy to clean and are disposable in the case of glass breakage.

rotor, 20-place

for capillaries for quantitative Buffy Coat Analysis, with lid (not suited for standard capillaries).



Cat. No. 2056

TECHNOLOGY

HAEMATOKRIT 210

Hematocrit centrifuge, without rotor		
Power supply *	208 – 240 V 1~	100 – 127 V 1~
Frequency	50 – 60 Hz	
Consumption	300 VA	220 VA
Radio interference	EN 55011 ISM class B	FCC class B
Immunity	EN 50082-1	-

Max. capacity	24/20 capillaries
Max. RPM (speed)	13,000 min ⁻¹
Max. RCF	16,060

Dimensions (H x W x D) in mm	247 x 275 x 330
Weight	approx. 10 kg

Cat. No.	2104	2104 – 01
----------	------	-----------

* other voltages on request

Andreas Hettich GmbH & Co. KG

Gartenstr. 100
D - 78532 Tuttlingen
Germany

www.hettichlab.com
info@hettichlab.com
service@hettichlab.com

Phone +49 (0)7461 / 705 - 0
Fax +49 (0)7461 / 705 - 125

National Sales: -200
International Sales: -201
National Service: -202
International Service: -203